

GLADIATOR[®] PRO

**THE EASIEST WAY
TO PREVENT CORROSION
IN THOUSANDS OF APPLICATIONS**



IBIX[®]
INDUSTRIAL

Innovative Solutions
for the Anticorrosion Coating Industry

GLADIATOR PRO FLAME SPRAY

Revolutionary Portable flame spray coating system for metal substrates, tanks, vessels, structural steel, concrete flooring, concrete tanks and other surfaces. The most efficient technology to prevent surface corrosion by applying eco-friendly thermoplastic coating systems on site.

Gladiator PRO is:

- compact
- portable, easy to carry
- easy to use
- versatile thanks to three application gun sizes with different flow rates and available in different versions (featuring straight flow or wide spray pattern), fully interchangeable
- the application process can be easily controlled by means of fast settings

SYSTEM DESCRIPTION AND TECHNICAL DATA:

- Mobile unit with large wheels for easier transport on rough terrain
- Quick connect, colour coded hoses to machine (9 m. long with possible 6 m. optional extension)
- Just requires LPG (3 bar pressure) and compressed dry air (1000 l/ min (40 cfm) or more)

Overall dimensions:

Installed machine max height:	1030 mm (40.55 in.)
Installed machine max width:	760 mm (29.92 in.)
Weight of the machine (with empty tank):	55 kg approx. (121 lbs)
Weight (empty tank):	25 kg (55 lbs)
Weight of full tank only:	35 kg approx. (77 lbs)



NEW "CENTURION" GUN

THE MOST POWERFUL GUN OF ITS TIME POWERED BY IBIX®

WIDER SPRAY PATTERN (over 10 cm. with the Large CENTURION gun) offering:

- faster spraying and more uniform layers (bigger powder flow spread over a much larger area)
- easier overlapping of passes and better powder flowing out
- no powder "lines" or "stripes"
- minimizes the risk of un-molten powder with air trapped in the coating

ACCESSORIES

- Infrared pyrometer with laser pointer to remotely check at all times the preheating temperature and the coating temperature of the object being treated
- Quanix thickness gauges: non-destructive gauges to measure the thickness of coating on either ferrous or non-ferrous substrates
- Preheating auxiliary systems, useful for coatings on particularly thick structures or in extremely cold weather conditions



CASE HISTORY

The **Gladiator PRO** Flame-Spraying System applies several kinds of thermoplastic powders – PolyHotCote, Polyfusion, PP, for instance.

These anti-corrosive coatings are long lasting, highly resistant to the sun, sand, salt deposits, water and air and chemical pollutants in general

IBIX® thermoplastic powders such as PolyHotCote, Polyfusion, etc. do not require any primer and they can be used for functional anti-osmotic, anti acid, anti abrasion coatings; also available in non-slip versions.




Anti-osmotic barrier

- for outdoor structures such as buildings/constructions, bridges, off-shore sector, nautical applications

Continuous dielectric insulation

- protective coating against stray currents for articles to be buried
- electrical and marine corrosion protection



Chemical resistance

- anti-acid coating for tanks, containers, fittings, industrial plants

Abrasion resistance

- abrasion-resistant coatings, high mechanical strength
- coatings for ducts to discharge mineral waste and process water



REVOLUTIONARY FLAME SPRAY COATING SYSTEM FOR CONCRETE FLOORING, CONTAINMENT TANKS AND OTHER CONCRETE ITEMS

The **Gladiator PRO** flame spray coater is a revolutionary coating system that virtually eliminates all of traditional plaster and paint coating shortcomings. It is resistant to chipping, peeling and scratching. It dries in seconds and is extremely durable.

Gladiator PRO flame spray coater was specifically designed to produce a polymeric anti-osmotic coating using our IBIX® POLYFUSION system following our recommended application cycle.

The finishes are easily applied with our proven application methods and the end result is a smooth and durable astoundingly beautiful finish, that will last for many years to come.

IBIX® POLYFUSION coatings offer:


- Long term protection
- UV resistance
- Anti-osmotic barrier
- Flexibility
- Repairability
- Excellent adhesion thanks to the special epoxy primer sealing the concrete substrate

The New "Centurion" Wide Spray gun allows **Gladiator PRO** to offer extremely high flame spray coating speeds on concrete substrates.




NEW EXTRA-COOLING SYSTEM with heat exchanger for prolonged flame spraying.

STANDARD COLOR CARD



RAL 7001



RAL 7035



RAL 7046




RAL 7016



RAL 1015



RAL 6005



RAL 9016



RAL 5017



RAL 3020

Examples of special colors :



Other colors available upon request.

IBIX SRL

Via dell'Industria, 43

48022 Lugo (RAVENNA) - ITALY

Tel. +39 0545 994589 - Fax +39 0545 994567

info@ibixindustrial.com - www.ibixindustrial.com